

APC Smart-UPS On-Line (SRT10KXLI)

Smart-UPS SRT 10000VA 230V



Price details:

Price excl. VAT: 4,431.46 €

Eco fees: 0.08 €

VAT 21 %: 930.62 €

Product details:

Product code: SRT10KXLI

EAN: 0731304304272

Manufacturer: APC

PDF generated on: 24 March, 2017



5,362.16 €

* VAT included

APC Smart-UPS On-Line, 10 kW /10 kVA, Input 230V /Output 230V, Interface Port Contact Closure, RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB, Extended runtime model

Includes: CD with software, Documentation CD, Installation guide, Temperature Probe, USB cable, Warranty card

Main specifications:

Power

Output power capacity:	10000 VA
Output power:	10000 W
Input operation voltage (min):	100 V
Input operation voltage (max):	476 V
Output operation voltage (min):	220 V
Output operation voltage (max):	240 V
Power supply input frequency:	40/70 Hz
Surge energy rating:	480 J
Efficiency:	94.6 %
Emergency Power Off (EPO):	Y
Crest factor:	3:1
Output frequency regulation:	50/60 Hz

Ports & interfaces

AC outlets quantity:	10
AC outlet types:	C13 coupler, C19 coupler
USB port:	Y
Serial interface:	Y
Serial interface type:	RJ-45
Number of output IEC jumpers:	3
SmartSlot:	Y

Battery

Battery technology:	Sealed Lead Acid (VRLA)
Battery recharge time:	1.5 h
Typical backup time at half load:	11.5 min
Typical backup time at full load:	3.8 min
Replacement battery cartridge:	APCRBC140
Hot-swap battery:	Y
Cold start:	Y
Automatic battery test:	Y
Battery life (max):	5 year(s)
Battery capacity:	1805 VAh

Design

Form factor:	Rackmount/Tower
Colour of product:	Black
International Protection (IP) code:	IP20
Performance	
UPS topology:	Double-conversion (Online)
Number of output phases:	1
Waveform:	Sine
Auto-restart:	Y
Noise level:	55 dB
LED indicators:	Y
Audible alarm(s):	Y
Technical details	
Input connections:	Hard Wire 3 wire (1PH+N+G), Hard Wire 5-wire (3PH + N + G)
Operational conditions	
Operating temperature (T-T):	0 - 40 °C
Storage temperature (T-T):	-15 - 45 °C
Operating relative humidity (H-H):	0 - 95 %
Storage relative humidity (H-H):	0 - 95 %
Operating altitude:	0 - 3000 m
Non-operating altitude:	0 - 15000 m
Certificates	
Certification:	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE, REACH
RoHS compliance:	Y
Energy Star certified:	Y
Weight & dimensions	
Width:	263 mm
Depth:	715 mm
Height:	432 mm
Weight:	111820 g
Package width:	600 mm
Package depth:	1000 mm
Package height:	461 mm
Package weight:	126820 g
Packaging content	
Quick installation guide:	Y
Cables included:	USB cable
Warranty card:	Y
Software CD:	Y
Temperature sensor:	Y
Packaging content:	
Other features	
Interface:	RJ-45 10/100 Base-T
Nominal output voltage:	230 V
Nominal input voltage:	230 V

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.